

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

5           Claims 1-11 (canceled)

12.       (previously presented) A method of making a perfect bound book having a book block comprising a multiplicity of paper pages, a double laminated cover having a paper cover, an inner lamination and an outer lamination adhered to the inner and outer faces of said paper cover, said book block having one lateral edge thereof referred to as a spine, said method

10       comprising the steps of:

a.       forming said book block;

b.       laminating a suitable plastic film to the outer face of said cover so as to constitute said outer lamination;

15       c.       laminating a suitable plastic film to the inner face of said cover so as to constitute said inner lamination, said cover with said inner and outer laminations adhered thereto forming said double laminated cover;

20       d.       after laminating said double laminated cover, roughening at least the surface of a central portion of the inner face of said inner lamination so that said adhesive will effectively bind said spine to said inner lamination in the area of said central portion;

e.       applying an adhesive so as to be disposed between said spine and said central portion of the inner face of said double laminated cover upon binding of the book;

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

f. bringing said central portion of said double laminated cover and said spine of said book block into binding engagement with one another with said adhesive therebetween; and

g. clamping said double laminated cover to said book block proximate said spine so that said adhesive adheres said double laminated cover to said spine of said book block.

5

13. (canceled)

14. (previously presented) The method of claim 12 wherein said step of roughening said center portion of said double laminated cover comprises forming a multiplicity of cuts in said inner lamination.

10

15. (previously presented) The method of claim 14 wherein said step of forming said cuts in said inner lamination results in at least some of said cuts extending through said inner lamination so as to at least in part expose said paper cover to said adhesive.

16. (original) The method of claim 12 wherein said step of conditioning said central portion comprises scarifying said inner lamination.

15

17. (original) The method of claim 16 wherein said step of scarifying said inner lamination comprises forming a multiplicity of cuts in said inner lamination.

18. (original) The method of claim 17 wherein said step of forming said cuts in said inner lamination includes cutting through said inner lamination and at least partially into said paper cover.

20

19. (original) The method of claim 18 wherein said step of forming said cuts is performed by forcibly rolling a roller over the inner lamination in the area of said center portion

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

of said double laminated cover, said roller having a plurality of points on its outer periphery with said points forming cuts in said inner.

20. (original) The method of claim 18 wherein as said roller is moved with respect to said center portion with said roller points in contact therewith, said roller is counter-rotated in a direction opposite to the direction it rollingly engages the inner lamination.

21. (original) The method of claim 20 wherein said points at least in part pull portions of said inner lamination out of the plane of said inner lamination thereby to roughen the surface of said inner lamination in the region of said center portion of said double laminated cover.

22. (original) The method of claim 21 wherein said points engage said paper cover and as said points roll out of contact with said paper cover at least in part pull portions of said paper cover out of the plane of said paper cover.

23. (original) The method of claim 21 where by forming said cuts through said inner lamination, said adhesive may directly contact said paper cover in the region of said cuts.

24. (original) The method of claim 12 wherein said step of laminating said outer and inner laminations are done simultaneously with one another.

25. (currently amended) A method of printing a book on demand and of perfect binding said book, said book having a book block comprising a plurality of paper text pages, a double laminated cover having an inner face and an outer face and having an outer lamination of plastic film laminated to said outer face of said paper cover and an inner lamination of plastic film laminated to said inner face of said paper cover, said book block having one edge thereof constituting a spine, said method comprising the steps of:

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

- a. printing said text pages corresponding to said book;
- b. forming said book block from said text pages;
- c. printing said paper cover corresponding to said book being printed on demand;
- d. laminating said outer and inner laminations to the inner and outer faces of said  
5 paper cover;
- e. conditioning at least the surface of a portion of the inner face of said double  
laminated cover in an area to be adhered to said spine of said book block so as to  
facilitate adhesive binding of said spine of said book block with said double  
laminated cover in the area of said central portion, wherein said step of  
10 conditioning said portion of said inner cover comprises roughening at least the  
surface of said portion of said inner lamination of said double laminated cover;
- f. applying a suitable adhesive so as to be disposed between said spine of said book  
block and said portion of said laminated cover to be adhered to said spine;
- g. bringing said spine and said conditioned portion of said double laminated cover  
15 into adhesive binding relation so that said adhesive adheres directly to said  
conditioned portion of said cover; and
- h. clamping said double laminated cover to said book block proximate said spine for  
a time sufficient to effect binding of said book block to said cover so as to form a  
perfect bound book having a double laminated cover.

20 26. (Canceled)

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

27. (currently amended) The method of claim ~~26~~ 25 wherein said step of roughening said conditioned portion of said double laminated cover comprises scarifying said inner lamination.

28. (currently amended) The method of claim ~~26~~ 25 wherein said step of roughening  
5 said conditioned portion of said double laminated cover comprises forcibly rolling a roller over said inner lamination wherein said roller has a plurality of points thereon which penetrate at least in part into said inner lamination.

29. (original) The method of claim 28 wherein said roller is counter rotated as said roller is forcibly rolled over said cover.

10 30. (original) The method of claim 29 wherein said points on said roller form a multiplicity of cuts in said inner lamination.

31. (original) The method of claim 30 wherein upon forming said cuts, said points of said roller pull portions of said inner lamination in the region of said cuts out of the plane of said inner lamination thereby roughening said surface of said inner lamination.

15 32. (original) The method of claim 31 wherein said points of said roller penetrate through said inner lamination exposing said paper cover to said adhesive.

33. (original) The method of claim 31 wherein said points of said roller penetrate at least in part into said paper cover and pull at least portions of said paper cover out of the plane of said paper cover into said cuts.

20 34. (original) Apparatus for printing a perfect bound book on demand, said book comprising a book block having a multiplicity of paper pages, one edge of said book block constituting a spine, a soft paper cover, said cover having an outer face and an inner face, said

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

cover having an outer lamination adhered thereto and said inner face of said cover having an inner lamination adhered thereto, said inner face of said cover having a central portion adhesively bonded to said spine, said apparatus comprising:

- a. a text printer for printing on demand the text pages comprising said book block;
- 5 b. a cover printer for printing on demand said cover for said on demand printed book;
- c. a lamination station for laminating a plastic film to both the outer face and the inner face of said cover thus forming a double laminated cover;
- d. a cover conveyor conveying said cover from said cover printer to said lamination  
10 station;
- e. a carriage receiving said book block after said text pages have been printed by said text printer;
- f. said carriage transporting said book block along a work path from a receiving station in which said carriage receives said book block to an adhesive application station  
15 in which an adhesive is applied to said spine of said book block;
- g. said carriage transporting said book block from said adhesive application station to a binding station;
- h. said cover conveyor transporting said double laminated cover from said lamination station to a cover conditioning station;
- 20 i. said cover conditioning station conditioning a portion of the inner face of said double laminated cover so as to facilitate the adhesive binding of said double laminated cover to said spine of said book block;

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

j. said laminated cover conveyor transporting said double laminated cover to said binding stations such that said conditioned portion of said double laminated cover is substantially in register with said spine; and

k. said binding station having a binding clamp engageable with the outer face of said double laminated cover proximate said spine so as to forcibly clamp said double laminated cover to said book block with said spine being substantially in register with said conditioned portion whereby said adhesive binds said double laminated cover to said spine.

35. (original) Apparatus as set forth in claim 34 wherein said conditioning station comprises a roller movable transversely with respect to the direction of transport of said cover, said roller having a plurality of points thereon scarifying inner lamination of said conditioned portion as said roller rolls thereover.

36. (original) Apparatus as set forth in claim 35 wherein said roller has a plurality of points thereon which at least in part penetrate into said inner lamination.

37. (original) Apparatus as set forth in claim 36 wherein said roller is counter rotated as said roller engages said conditioned portion thereby to form a plurality of slits or cuts in said inner lamination.

38. (original) Apparatus as set forth in claim 37 wherein said conditioning station comprises a holder for rotatably mounting said roller, said holder being movable transversely across said cover, a friction wheel carried by said holder rollingly engageable with said cover as said holder is moved transversely across said cover, said friction wheel driving a gear in mesh

Appln No. 10/017,185  
Amendment Dated September 29, 2004  
Reply to Office Action of August 20, 2004

with a pinion affixed to said roller for counter-rotating said roller as said holder is moved with respect to said cover.